

**General Certificate of Education (A-level) June 2011** 

Design and Technology: Product Design

PROD1

(Specification 2550)

**Unit 1: Materials, Components and Application** 

## **Post-Standardisation**

Mark Scheme

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all examiners participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the candidates' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for standardisation each examiner analyses a number of candidates' scripts: alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, examiners encounter unusual answers which have not been raised they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of candidates' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this Mark Scheme are available from: aqa.org.uk

Copyright © 2011 AQA and its licensors. All rights reserved.

## Copyright

AQA retains the copyright on all its publications. However, registered centres for AQA are permitted to copy material from this booklet for their own internal use, with the following important exception: AQA cannot give permission to centres to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Set and published by the Assessment and Qualifications Alliance.


Question	Part	Sub Part	Marking Gu	uidance		Mark	Comments
1	а			of two or mor	re metals	2	2 or zero marks only
1	b		Stainless si Kitchen sin If alloy not a zero for (b)	k	correct award	1	Accept aluminium Alloy
2	Fabri on Meth	cati	Joining aluminium tube to aluminium tube to make a cycle frame	Joining copper to copper to make jewellery	Joining mild steel angle to mild steel angle to make a workbenc h frame Arc welding or MIG welding	1 1 1	One mark for each correct answer.  Note If candidate uses same fabrication method more than once – only award the mark once.
3	а			ed square ed vel, angle or	ge)	1	Accept: PAR, PBS, Planed, Rough sawn, Plank, Beam
3	b		to wear and years giving money.  E.g. Oak ha	n which suits ary tastes.	ill last many ner value for ve colour and	4	2 marks for each reason. Award 1 mark for one word answers e.g. "it's durable", "it's aesthetically pleasing".  Max 2 marks for list of properties
4	а		be reshape heat. It has that will refe	astic is a poly d by the app loose mono orm when he can be recyc	mer chains ated and	2	Must mention use of heat for 2 marks
4	b		E.g. ABS  Casing for	a vacuum cle	eaner	1	
5	Cutting value of the control of the	otter –	3D mack of a block MDF CNC Ro	ck of e a uter C	outting and ngraving crylic sheet NC laser utter <b>or</b> NC router	1 1 1	1 mark for each correct answer.  Note If candidate uses the same piece of equipment more than once – only award the mark once.

Question	Part	Sub Part	Marking Guidance	Mark	Comments
6	а	i	SMA reacts to temperature so when the braces are placed onto the teeth by the dentist, they will react to body temperature, contract and tighten  SMA is an inert material which is important as it will be used in the mouth so you would not want it to corrode or react to liquids  SMA such as Nitonol is a non toxic material and is therefore perfectly safe to use in the mouth.	6	Mark breakdown:  1-2 marks per point. Award second mark where explanation of the relevance of the property is given.  Accept ref to aesthetic qualities of Nitonol.  Generic list max 3 marks.
6	а	ii	Photo quality paper will give a high gloss which is necessary for a professional finish on point of sale displays. (Ref to printing qualities)  Photo quality paper can be laminated onto a card or polymer backing that the POS display might be constructed from  Photo quality paper is made from sustainable sources so its environmental impact can be kept to a minimum.  Recycling	6	Mark breakdown:  1-2 marks per point. Award second mark where explanation of the relevance of the property is given.  Accept ref to making techniques including hand and commercial methods.
6	а	iii	Polymorph granules bonds together with the application of gentle heat (approx 60 degrees) so they can be easily shaped.  Polymorph will give a similar finish to injection moulded polymer which is useful to show users/clients.  E.g. Polymer can be painted to simulate the colours of an injection moulded product.  Ignore references to a production version e.g. toxicity.	6	Mark breakdown:  1-2 marks per point. Award second mark where explanation of the relevance of the property is given.  Accept ref to re-using or reshaping to make further models.
6	b		MDF It can be shaped easily into the form of a handle by cutting with hand tools and sanding with glass paper.	2	Accept appropriate alternatives e.g. foamboard Styrofoam, clay, plastecine or modeling clay, resin, model board. Balsa, Acrylic, RPT material etc.  1 mark for material 1 mark for reason

Question	Part	Sub Part	Marking Guidance	Mark	Comments
7	а		E.g. Stainless steel	1	(Accept mild steel or aluminium) Duralumin
7	b		<ul> <li>E.g. Stainless steel is a very hard material and will withstand attempts at vandalism e.g. scratching.</li> <li>E.g. Stainless steel does not corrode and therefore will withstand the effects of weather.</li> <li>E.g. Stainless steel has an attractive silver colour which looks appealing in a modern street environment.</li> </ul>	6	Mark breakdown:  1-2 marks per reason. Award second mark where explanation is given for relevance of the property.  If no metal named in (a), award zero for (b).  If unsuitable metal award marks for relevant properties.
7	C		<ul> <li>Answer may include notes and diagrams of the following:         <ul> <li>Cutting bar/tube to length with power hacksaw with a stop/ in a cutting jig to remove need for measuring. Alternatively buy in steel cut to length.</li> <li>Bending of tube (in pipe bender), bar over a jig or fixture following heat treatment.</li> <li>Clamping of parts together. Possible use of jigs/fixtures/spacers to achieve consistent parallel parts.</li> </ul> </li> <li>May describe welding process but only award upto half marks if no ref to batch production.</li> <li>Ignore ref to manufacture of the bars e.g. extrusion.</li> </ul>	9	Wery simple diagram with inaccurate and basic description e.g. hand cutting with 'saw', basic torch flame and generic 'welding' given, no reference to batch production. (0-3 marks)  Better diagram showing some further detail e.g.clamps, welding rod and torch (if gas welding described). Possibly names 'electric arc' welding and may confuse between several different methods. (4-5 marks)  Diagrams and notes make reference to batch production e.g. clamping over former/welding fixture. (6-7 marks)  A more detailed answer with ref to cutting stops, bending fixture, comparing parts to drawing or 'standard parts', welding jig, spacers and so on. (8-9 marks)

Question	Part	Sub Part	Marking Guidance	Mark	Comments
7	d		A welding visor is used to protect the eyes from the UV light caused by the flash of the electric arc.  Extractors are used to remove toxic gases from the welding area.  Personal protective clothing e.g. gloves, overalls and safety boots to protect from cuts, oils, etc. (note only 1 mark for a list of different PPC).  Training of workers to prevent accidents. Familiarise workers with risk assessments.	4	Mark breakdown:  1-2 marks per precaution. Award the second where the reason for the precaution is given.
8	а	i	Accept :Polypropylene (PP), Low Density Polyethylene (LDPE), High Density Polyethylene HDPE, PET, Thermoplastic Elastomer (TPE). Not PVC, Not ABS, Not Acrylic, Not PS/Hips	1	
8	a	ii	E.g. Polypropylene is a thermoplastic which can be extrusion blow moulded which is the most likely process to manufacture the bottle.  E.g. PP can be given a variety of pigments to colour the product for aesthetic purposes  E.g. P.P is lightweight which is good as the liquid contents would make it heavy to carry anyway.  Alternatives might include ref to material being non toxic, highly durable to withstand the rigours of running, impact resistant because should items would be dropped, etc.  N.B. Don't penalise if thermoplastic in (ai) is incorrect, award marks for relevant properties of named plastic in (ii).	6	Breakdown: 1- 2 marks per relevant point. 2 marks where point is explained or further detail given.  If generic list max 3 marks.  N.B. Don't double penalise if thermoplastic in (a)i is incorrect, award marks for relevant properties of named plastic in (ii).

Question	Part	Sub Part	Marking Guidance	Mark	Comments
8	а	iii	Accept only extrusion blow moulding or blow moulding from a hollow bottle shaped preform.  The polymer is extruded in a tube form known as a 'Parison'. The mould halves close on the 'Parison' and trap the base together. Air is blown into the Parison which is forced out to the sides of the mould where it cools. The moulds open, releasing the product. Flash is removed.  If injection blow moulding is described, award marks only up to middle mark band (see additional notes) (max 6)	9	Mark breakdown:  Simple description with little detail. Diagrams are basic with incorrect labels or incomplete parts (0-4 marks)  Better description using correct terminology. Diagram mostly complete and correct (5-6 marks)  Full description. Correct /complete diagram. Detail includes terminology e.g. (7-9 marks)



Question	Part	Sub Part	Marking Guidance	Mark	Comments
8	b		Answers will be varied but may include in their notes and diagrams details as follows:  Product will need to fit the palm line for the 50 <sup>th</sup> percentile. Maybe comments that it appears too wide.  Texture on the sides to aid grip whilst running  Shaping on edges to hold firmly whilst running. Some may suggest modification e.g. centre moulded to fit hand through or moulded in handle on the side.  Some may suggest the addition of handle/body coated with LSR/TPE to provide additional grip.  The top has a textured edge so that it is easy to grip and undo for filling up.  The bottle has been fitted with a gauge to show full the product is, or to measure out specific sports drink ingredients.  The bottle top is made from TPE or LSR which is soft to the lips.  The pull top is designed to be opened by the user's teeth.  Standardised shape to fit in a variety of carriers/holders  Polymer is lightweight and therefore easy to carry	10	Mark breakdown:  Basic diagrams. Largely descriptive comment with very little analytical. (0-3 marks)  Better diagrams. Some analytical comment. (4-7 marks)  Clear diagrams, appropriately annotated with good analytical comment. (8-10 marks)  IF NO DIAGRAMS MAX (5 marks)  IGNORE REFERENCES TO COLOUR.

Question	Part	Sub Part	Marking Guidance	Mark	Comments
8	C		Peatures that add value e.g. re use of the package, cooler, zipped bag, etc.  Reducing the materials  Use of recycling/ recycling materials including starch based polymers.  Printing of the recycling symbol  Use of colours and logos to attract customers  Use of the euro slot to hang packaging  How the package will be manufactured e.g. staples; crimping of plastic sides, etc.  Biodegradable materials	14	Mark breakdown:  Basic diagrams with few of the criteria listed in the question addressed. Simple notes about the material, making process and obvious statement about the environment. e.g. Drawing of simple 'card' box with little styling detail. Made by cutting and folding card. 'Can be recycled'. (0-4 marks)  Better design with some styling/shaping to the package. Possibly specific material(s) named. Technical terms used such as 'net', scoring, etc. may describe using recycled materials. (5-9 marks)  Clear diagram(s) with an appropriate design for the package with aesthetic appeal. Some innovative features in the styling/method of holding the bottle. Specific material(s) named. Technical terms for manufacturing/finishing e.g. press-knife, off-set litho or digital printing, description of using less material, recycled/recyclable material, eco-friendly inks, etc. If plastic bag —starch based polymers used. (10-14 marks)