Version: 1.0: 0206



General Certificate of Education

Mathematics 6360

MM2A Mechanics 2A

Mark Scheme

2005 examination - June series

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation meeting attended by all examiners and is the scheme which was used by them in this examination. The standardisation meeting ensures that the mark scheme covers the candidates' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for the standardisation meeting each examiner analyses a number of candidates' scripts: alternative answers not already covered by the mark scheme are discussed at the meeting and legislated for. If, after this meeting, examiners encounter unusual answers which have not been discussed at the meeting they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of candidates' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Key to mark scheme and abbreviations used in marking

M mark is for method

m or dM mark is dependent on one or more M marks and is for method M mark is dependent on M or m marks and is for accuracy

B mark is independent of M or m marks and is for method and accuracy

E mark is for explanation

√or ft or F follow through from previous

incorrect result MC mis-copy
CAO correct answer only MR mis-read
CSO correct answer only MR mis-read

CSO correct solution only RA required accuracy AWFW anything which falls within FW further work

AWRT anything which rounds to **ISW** ignore subsequent work any correct form **ACF FIW** from incorrect work answer given given benefit of doubt AG **BOD** SC special case WR work replaced by candidate

OE OE FB formulae book A2,1 2 or 1 (or 0) accuracy marks NOS not on scheme -x EE deduct x marks for each error G graph

NMSno method shownccandidatePIpossibly impliedsfsignificant figure(s)SCAsubstantially correct approachdpdecimal place(s)

Application of Mark Scheme

No method shown:

Correct answer without working mark as in scheme

Incorrect answer without working zero marks unless specified otherwise

More than one method / choice of solution:

2 or more complete attempts, neither/none crossed out mark both/all fully and award the mean

mark rounded down

1 complete and 1 partial attempt, neither crossed out award credit for the complete solution only

Crossed out work do not mark unless it has not been replaced

Alternative solution using a correct or partially correct method award method and accuracy marks as

appropriate

MM2A/W

| Q | Solution | Marks | Total | Comments |
|------|---|------------|-------|--|
| 1(a) | $12.5 = \lambda \times \frac{0.1}{0.4}$ | M1A1 | | M1: subs. A1: All correct |
| | $\lambda = 50$ | A1 | 3 | |
| (b) | $EPE = \frac{50 \times (0.1)^2}{2 \times 0.4}$ | M1 | | Subs. |
| | $= 0.625 \mathrm{J}$ | A1 | | PI A1: all correct |
| | $0.625 = \frac{1}{2} \times 0.2 \times v^2$ | M1 | | M1 use of principle |
| | $0.023 - \frac{1}{2} \times 0.2 \times V$ | A1F | | ft EPE |
| | $v = 2.5 \text{ ms}^{-1}$ | A1F | 5 | ft EPE |
| | Total | | 8 | |
| 2(a) | 90g 35g 60 F | B1 | 1 | All forces shown and in correct direction (no extras) |
| (b) | R = 125g (=1225) | B1 | | |
| | $F = 0.3 \times R$ | M1 | | Condone inequality |
| | F = 367.5N | A1F | 3 | ft slip, both vertical forces present (g missing B0 M1 A1F) |
| (c) | M (ground) | | | |
| | $35g \times 1.5\cos 60^{\circ} + 90g \times x \times \cos 60^{\circ}$ $= N \times 3\cos 30^{\circ}$ | M1A2 | | M1 attempt at moments eqn., accept one force missing1 each term missing or incorrect. Condone repeated error, <i>g</i> missing or sin/cos mix. |
| | F = N | B1 | | |
| | Substitute to find <i>x</i> | m1 | | Subs. of candidate's N |
| | x = 1.582 metres | A 1 | 6 | Accept 1.6 |
| | Total | | 10 | |

www.theallpapers.com

MM2A/W (cont)

| Q | Solution | Marks | Total | Comments |
|---------|---|----------|-------|---|
| 3(a)(i) | $T\cos 60^{\circ} = 0.4g$ | M1A1 | | |
| | T = 7.84 newtons | A1 | 3 | AG |
| (b) | $T\cos 30^\circ = 0.4 \ \omega^2 r$ | M1A1 | | |
| | $r = \tan 60^{\circ}$ | B1 | | |
| | $7.84 \times \cos 30^{\circ} = 0.4 \ \omega^{2} \times \tan 60^{\circ}$ | m1 | | Subs |
| | $\omega = 3.13$ | A1 | 5 | AG |
| (c) | $T = \frac{2\pi}{\omega} = 2.007$ | | | |
| | ≈ 2 sec | B1 | 1 | |
| | Total | | 9 | |
| 4(a) | $M(A)4Mg \times \frac{3d}{2} + Mg \times 2d = 5Mg \times \overline{y}$ | M1A2 | | M1 3 terms (M1 A0 if areas used) Condone ratio methods for weights1 each term wrong |
| | $\overline{y} = 1.6d$ | A1 | 4 | $M(AB) 4Mg \times \frac{3d}{2} + Mg \times 2d = 5Mg \times y$ |
| (b) | D = 2.4d G | | | |
| | $\tan \theta = \frac{GM}{CM}$ | M1 | | Full method for an acute angle involving wallet |
| | $=\frac{2.4d}{3d}$ | A1A1 | | A1A0 for inverse |
| | $\theta = 38.7^{\circ}$ | A1F | 4 | ft slip in subtraction |
| | Total | | 8 | |
| 5 | $\frac{\mathrm{d}v}{\mathrm{d}t} = \frac{k}{v}$ | B1 | | |
| | $\int v dv = \int k dt$ | M1 | | Separation of variables involving t |
| | $\int v dv = \int k dt$ $\frac{v^2}{2} = kt + c$ | m1 A1 | | Integrate |
| | $t = 0, \ v = u, \ \therefore c = \frac{u^2}{2}$ | m1 | | |
| | $v^2 = u^2 + 2kt$ | A1 | 6 | |
| | Total | | 6 | |

MM2A/W (cont)

| Q | Solution | Marks | Total | Comments |
|--------|---|-------|-------|---|
| 6(a) | $\mathbf{a} = 8\cos t\mathbf{i} - 4\sin t\mathbf{j}$ | M1A1 | | M1 differentiation |
| | $\mathbf{F} = 2\cos t\mathbf{i} - \sin t\mathbf{j}$ | A1 | 3 | |
| | | | | |
| (b)(i) | $\left \mathbf{F}\right = \sqrt{(4\cos^2 t + \sin^2 t)}$ | M1 | | Magnitude |
| | $ \mathbf{F} = \sqrt{(4\cos^2 t + \sin^2 t)}$ $= \sqrt{(3\cos^2 t + 1)}$ | m1 | | |
| | · | A1 | 3 | CAO |
| | | | | |
| (ii) | $I \leq \mathbf{F} \leq 4$ | B1B1 | 2 | B1 each value (at end of range) |
| | Total | | 8 | |
| 7(a) | $\frac{1}{2}mU^2 = mga$ $U = \sqrt{(2ga)}$ | M1A1 | | Conservation of energy for M1 $v = 0$ for A1 |
| | $U = \sqrt{(2ga)}$ | A1F | 3 | ft slip (eg $h = 2a$) |
| | | | | |
| (b) | 70 | | | |
| | a e h | | | |
| | $R = 0 : mg \cos \theta = \frac{mv^2}{a}$ | M1A1 | | M1 for $F = ma$ in general position |
| | $v^2 = ag \times \frac{h}{a} \qquad v^2 = ag \times \frac{h}{a}$ | m1 | | Subs for $\cos \theta$ |
| | $v^2 = hg v^2 = hg$ | A1F | | ft errors in height |
| | $\frac{1}{2}m\left(\frac{5ag}{2}\right) = \frac{1}{2}mv^2 + mgh$ | M1A1 | | M1 conservation of energy using u , v and h . |
| | $\frac{5ag}{2} = 3gh$ | m1 | | Subs for v^2 |
| | $h = \frac{5a}{6}$ | A1 | 8 | |
| | Total | | 11 | |
| | Total | | 60 | |

www.theallpapers.com