

MARK SCHEME for the May/June 2013 series

9709 MATHEMATICS

9709/42

Paper 4, maximum raw mark 50

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2013 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.

| | | | |
|--------|--------------------------------|----------|-------|
| Page 2 | Mark Scheme | Syllabus | Paper |
| | GCE AS/A LEVEL – May/June 2013 | 9709 | 42 |

Mark Scheme Notes

Marks are of the following three types:

M Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.

A Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated method mark is earned (or implied).

B Mark for a correct result or statement independent of method marks.

- When a part of a question has two or more “method” steps, the M marks are generally independent unless the scheme specifically says otherwise; and similarly when there are several B marks allocated. The notation DM or DB (or dep*) is used to indicate that a particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme. When two or more steps are run together by the candidate, the earlier marks are implied and full credit is given.
- The symbol \surd implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously “correct” answers or results obtained from incorrect working.
- Note: B2 or A2 means that the candidate can earn 2 or 0.
B2/1/0 means that the candidate can earn anything from 0 to 2.

The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.
- For a numerical answer, allow the A or B mark if a value is obtained which is correct to 3 s.f., or which would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers which arise from taking g equal to 9.8 or 9.81 instead of 10.

| | | | |
|---------------|---------------------------------------|-----------------|--------------|
| Page 3 | Mark Scheme | Syllabus | Paper |
| | GCE AS/A LEVEL – May/June 2013 | 9709 | 42 |

The following abbreviations may be used in a mark scheme or used on the scripts:

| | |
|-----|---|
| AEF | Any Equivalent Form (of answer is equally acceptable) |
| AG | Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid) |
| BOD | Benefit of Doubt (allowed when the validity of a solution may not be absolutely clear) |
| CAO | Correct Answer Only (emphasising that no “follow through” from a previous error is allowed) |
| CWO | Correct Working Only – often written by a ‘fortuitous’ answer |
| ISW | Ignore Subsequent Working |
| MR | Misread |
| PA | Premature Approximation (resulting in basically correct work that is insufficiently accurate) |
| SOS | See Other Solution (the candidate makes a better attempt at the same question) |
| SR | Special Ruling (detailing the mark to be given for a specific wrong solution, or a case where some standard marking practice is to be varied in the light of a particular circumstance) |

Penalties

| | |
|-------|---|
| MR –1 | A penalty of MR –1 is deducted from A or B marks when the data of a question or part question are genuinely misread and the object and difficulty of the question remain unaltered. In this case all A and B marks then become “follow through ✓” marks. MR is not applied when the candidate misreads his own figures – this is regarded as an error in accuracy. An MR –2 penalty may be applied in particular cases if agreed at the coordination meeting. |
| PA –1 | This is deducted from A or B marks in the case of premature approximation. The PA –1 penalty is usually discussed at the meeting. |

| Page 4 | Mark Scheme | Syllabus | Paper |
|--------|--------------------------------|----------|-------|
| | GCE AS/A LEVEL – May/June 2013 | 9709 | 42 |

| | | | | | |
|---|------|---|----|-----|---|
| 1 | (i) | [24 = μ 30] | M1 | [2] | For using $R = W$, $F = T$ and $F = \mu R$ |
| | | Coefficient is 0.8 | A1 | | |
| | (ii) | $F = 0.8(30 - 25\sin 30^\circ)$ (=14) | M1 | | For resolving forces vertically and using $F = \mu R$ |
| | | [25 cos 30° – F = (30 ÷ g)a] | A1 | | |
| | | Acceleration is 2.55 ms ⁻² | M1 | [4] | For using of Newton's 2nd law |
| | | | A1 | | |
| 2 | (i) | | M1 | [3] | For using work done by pulling force = increase in KE – decrease in PE + WD by resistance |
| | | $1150 = \frac{1}{2} 16 \times 10^2 - 16g(50 \times 0.05)$ + WD by resistance | A1 | | |
| | | WD by resistance = 750 J | A1 | | |
| | (ii) | $1150 = \text{increase in KE} + 16 g(50 \times 0.05) + 750$ | M1 | | For WD by pulling force = KE gain + PE gain + WD by resistance |
| | | KE gain = 0 → speed at top = speed at bottom | A1 | [2] | AG |
| 3 | | | M1 | [5] | For resolving forces acting on P horizontally or vertically |
| | | $T_A \times (40/50) + T_B \times (40/104) = 21$ or $T_A \times (30/50) = T_B \times (96/104)$ | A1 | | |
| | | $T_A \times (30/50) = T_B \times (96/104)$ or $T_A \times (40/50) + T_B \times (40/104) = 21$ | B1 | | |
| | | Solve for T_A and T_B | M1 | | Solving for both |
| | | Tension in AP is 20 N and tension in BP is 13 N | A1 | | Both $T_A = 20$ and $T_B = 13$ |
| First Alternative Marking Scheme | | | | | |
| 3 | | | M1 | | For using the sine rule in the triangle of forces |
| | | $21/\sin 75.75$ (or 75.7 or 75.8) = $T_A/\sin 67.4$ (or $T_B/\sin 36.9$) | A1 | | |
| | | $21/\sin 75.75$ (or 75.7 or 75.8) = $T_B/\sin 36.9$ (or $T_A/\sin 67.4$) or $T_B/\sin 36.9 = 20/\sin 67.4$ | B1 | | |
| | | Solve for T_A and T_B | M1 | | Solving for both |

| | | | |
|---------------|---------------------------------------|-----------------|--------------|
| Page 5 | Mark Scheme | Syllabus | Paper |
| | GCE AS/A LEVEL – May/June 2013 | 9709 | 42 |

| | | | | |
|--|--|--|-----|--|
| | Tension in AP is 20N and tension in BP is 13N | A1 | [5] | Both $T_A = 20$ and $T_B = 13$ |
| Second Alternative Marking Scheme | | | | |
| 3 | $21/\sin 104.3 = T_A/\sin 112.6$ (or $T_B/\sin 143.1$) $21/\sin 104.3 = T_B/\sin 143.1$ (or $T_A/\sin 112.6$) or $T_B/\sin 143.1 = 20/\sin 112.6$ or $T_A/\sin 112.6 = 13/\sin 143.1$ Solve for T_A and T_B Tension in AP is 20 N and tension in BP is 13 N | M1 A1 B1 M1 A1 | [5] | For using Lami's Rule For using the equations to find T_A and T_B Both $T_A = 20$ and $T_B = 13$ |
| 4 (i) | $a = (16 \div 65)g$ $[8^2 = 2(16 \div 65)gS]$ $S = 13$ $[v^2 = 2(16 \div 65)g \times 6.5$ or $v^2 \div 8^2 = 1/2]$ Speed is 5.66 ms^{-1} | B1 M1 A1 M1 A1 | [5] | For using $v^2 = 2as$ to find S For using $v^2 = 2a(1/2S)$ or $v^2 \propto s$ |
| (ii) | $[s = 1/2 a \times (64 \div 4a^2)$ or $s \div 13 = (1/2)^2]$ Distance is 3.25 m | M1 A1 | [2] | For using $8 = 0 + aT$ and $s = 1/2a(T/2)^2$ or $s \propto t^2$ |
| Alternative Marking Scheme | | | | |
| 4 (i) | $[1/2 m v^2 = mgh$ and $S = h \div \sin \alpha$ $S = (8^2 \div 20) \div (16 \div 65)$ $S = 13$ $1/2 m v^2 = mg(1/2 \times 13 \times (16/65))$ Speed is 5.66 ms^{-1} | M1 A1 A1 M1 A1 | [5] | For using KE gain = PE loss Or AEF Or AEF |
| (ii) | Distance is 3.25 m | M1 A1 | [2] | For eliminating t^2 from $s = 1/2at^2$ and $13 = 1/2a(2t)^2$ |
| 5 (i) | Driving force = 1000P/25 | B1 | | |

| | | | |
|---------------|---------------------------------------|-----------------|--------------|
| Page 6 | Mark Scheme | Syllabus | Paper |
| | GCE AS/A LEVEL – May/June 2013 | 9709 | 42 |

| | | | | |
|---|--|------|-----|---|
| | | M1 | | For using Newton's 2 nd law |
| | $1000P/25 - 600 = 1000 \times 0.2$ | A1 | | |
| | $P = 20$ | A1 | [4] | |
| (ii) | | M1 | | For using Newton's 2 nd law with $a = 0$ |
| | $20000/v_{\max} - 600 = 0$ | A1ft | | ft for their P in (i) |
| | Steady speed is 33.3 ms^{-1} | A1 | [3] | |
| 6 (i) | For sketch of single valued, continuous graph consisting of 3 straight line segments with + ^{ve} , then - ^{ve} , then + ^{ve} slope | B1 | | |
| | Sketch appears to show $v(0) = 0$ and $v(8) > v(26) > v(20)$ | B1 | [2] | |
| (ii) | For shading the triangle from $t = 0$ to $t = 8$, the trapezium from $t = 8$ to $t = 20$ and the trapezium from $t = 20$ to a value of t seen to be between 20 and 26 | B1 | [1] | |
| (iii) | | M1 | | For using area property to find $s(20)$ |
| | $s(20) = \frac{1}{2}(8 \times 8) + \frac{1}{2}(8 + 2) \times 12 \quad (= 92)$ | A1 | | |
| | | M1 | | For using the gradient property to find acceleration in 3 rd phase |
| | $a = (6.5 - 2)/6 \quad (= 0.75)$ | A1 | | |
| | $[s(t) = 92 + 2(t - 20) + 0.375(t - 20)^2$ | M1 | | |
| | Displacement is $0.375t^2 - 13t + 202$ metres | A1 | [6] | |
| Alternative Marking Scheme for final 2 marks of Q6 | | | | |
| | $[v(t) = 2 + 0.75(t - 20)$ $s(t) = 0.375t^2 - 13t + A$ where $92 = 0.375 \times 400 - 13 \times 20 + A]$ | M1 | | For finding $v(t)$, integrating and using $s(20) = 92$ |
| | Displacement is $0.375t^2 - 13t + 202$ metres | A1 | | |
| 6 (iii) | First Alternative Marking Scheme for part (iii) of Q6 | | | |
| | $a = (6.5 - 2) / (26 - 20) = 0.75$ | B1 | | |
| | $v = 0.75t (+ C1)$ | M1 | | Integrating |
| | $v = 0.75t - 13$ | A1 | | Using $v(20) = 2$ or $v(26) = 6.5$ |

| Page 7 | Mark Scheme | Syllabus | Paper |
|--------|--------------------------------|----------|-------|
| | GCE AS/A LEVEL – May/June 2013 | 9709 | 42 |

| | | | | |
|----------------|---|--|-----|---|
| | $s(20) = 92$ or $s(26) = 117.5$ $s = 0.375t^2 - 13t (+ C_2)$ $s = 0.375t^2 - 13t + 202$ | B1 M1 A1 | [6] | Using area in diagram Integrating Using $s(20)$ or $s(26)$ to find $C_2 = 202$ |
| 6 (iii) | Second Alternative Marking Scheme for part (iii) of Q6 | | | |
| | $s = 0.375t^2 - 13t + 202$ $v = 0.75t - 13$ $a = 0.75$ $a = (6.5 - 2)/(26 - 20) = 0.75$ $v(20) = 0.75(20) - 13 = 2$ or $v(26) = 0.75(26) - 13 = 6.5$ Show $s(20) = 92$ or $s(26) = 117.5$ $s(20) = 0.375(20)^2 - 13(20) + 202 = 92$ or $s(26) = 0.375(26)^2 - 13(26) + 202 = 117.5$ | M1 M1 B1 B1 B1 B1 | | Given Differentiating Differentiating Check agreement from graph Check v agrees at a point between $t = 20$ and $t = 26$ Using area under graph Check s agrees at a point between $t = 20$ and $t = 26$ |
| 7 (i) | $T - 0.26g(16 \div 65) = 0.26a$ or $0.52g - T = 0.52a$ For $\{0.52g - T = 0.52a$ or $T - 0.26g(16 \div 65) = 0.26a\}$ or $0.52g - 0.26g(16 \div 65) = (0.52 + 0.26)a$ Acceleration is 5.85 ms^{-2} Tension is 2.16 N | M1 A1 B1 B1 A1 | [5] | For applying Newton's 2 nd law to A or B |
| (ii) | $[v^2 = 2 \times (76/13) \times 0.6]$ Speed is 2.65 ms^{-1} $0 = 91.2/13 - 2(160/65)s$ $S = 57/40 (= 1.425)$ $[AP = 2.5 - 0.6 - 1.425]$ Distance AP is 0.475 m | M1 A1 M1 A1 M1 A1 M1 A1 | [6] | For using $v^2 = 2as$ For using $0 = v_B^2 - 2(g \sin \alpha)s$ For using $AP = 2.5 - 0.6 - s$ |